



WEIFANG RONSUN POWER TECHNOLOGY CO., LTD.

Address: No.6699 Weizhou Road, Fangzi District, Weifang City, Shandong Province, China.

CUMMINS 75kVA /60kW Diesel Generator Quotation




To:	Gustavo Muñoz		
Voltage	110/220V	Efficiency	≥85%
Frequency	60Hz	Insulation Class	H
Power Factor	0.8	Certificate	CE & ISO
Phase	3 Phase, 4 Wire		
Protection Grade	IP23		
FOB QINGDAO price: USD10,170/SET			

SPECIFICATION:

Gen-set	Model		75GF
	Type		Trailer Type
	Prime Power (kW/kVA)		60/75
	Stanby Power (kW/kVA)		66/82.5
	Packing Size	Length (mm)	2100
		Width (mm)	1000
		Height (mm)	1700
Gross Weight (kg)		1300	

Diesel Engine	Model		4BTA3.9-G2
	Brand		CUMMINS
	Year of production		2024
	Fuel		Diesel
	Rated Speed (RPM)		1800
	Intake Type		Turbocharged
	Cylinder No.		4.L
	Compression Rate		17.3 : 1
	Bore×Stroke (mm)		102x120
	Displacement (L)		3.9
	Rated Fuel Consumption (L/h)100%		15.9L/H
	Rated Fuel Consumption (L/h)75%		12.2L/H
	Rated Fuel Consumption (L/h)50%		8.7L/H
	Lub Oil Capacity (L)		10.9
Governing Type		Electrical Governor	
Electrical Governor Rate		≤1%	

	Mechanical Governor Rate	≤5%
	Start Method	DC24V Electric Motor
Alternator	Brand	STAMFORD
	Model	UCI224F14
	Rated Power (kW/kVA)	60/75
	Excitation Type	Brushless, Self-excited
	Voltage Regulation	AVR
	Insulation Class	H
Controller	Brand	Deepsea
	Model	DSE6110
	Main Protection Function	Fail to Start/Low Oil Pressure/High Speed /Low Frequency/Low Voltage/High Voltage /High Temperature/Over Frequency
	Main Display Parameter	L-L&L-N Voltage/Load Current /Frequency/Speed/Oil Pressure/ Running Hours/Load Power /Coolant Temperature
		
Other Terms	ATS	Automatic transfer switching
	Delivery Time	Within 20 working days after the deposit
	Payment Terms	30% Downpayment, 70% Balance paid before shipment
	Warranty	1 Year or 1500 Running Hours (Whichever comes first)
	Supply Scope	Diesel Engine
		Soundproof Canopy
		AC 3 Phase Synchronous Alternator
		Muffler
		Fan and Radiator
		Controller cabinet
Battery connect Cable		
Spare parts: Oil filter 2pcs / air filter 1pc		